DRAIN PUMPS

Type PJV

SAGInoMIYA

GENERAL DESCRIPTION

- Drain pump which can exhaust drain water in accumlating at indoor unit.
- By adopting a high durable and power motor, this realizes much higher durability, low noise and high pump head.
- Mounting bracket is supplied as standard.
- Fluid: Drain water
- Fluid temp.: 0 to 35°C (No frozen water)
- Ambient temperature: −10 to 45°C
- Motor coil insulation: Class “E”
- Brackets are available upon request.

TYPE NUMBER SELECTION (SPECIFICATIONS)

Catalg No.	Rated Voltage	Power Consumption (50/60Hz)	Max. Flow	Pump Head (mm)	Sound Level	Wt. (kg)
PJV–0718	220 to 240V. AC ±10% 50/60Hz	8/7.5W 60/50mA	400cm³/min or More	500	36dB (A) or less on no drain	0.6
PJV–0726						
PJV–1008				750		
PJV–1412		12/11W 110/90mA		1125		

DIMENSIONS

Type PJV–0718, 0726, 1008

Type PJV–1412

D=60 (Type PJV–0718, 0726)
D=64 (Type PJV–1008)

Unit: mm

NOTE FOR USE

* It must be 8mm (10mm: PJV–1412) or more the distance from drain pan to the tip of suction opening of the pump.